Depth-DJ



Application

• Di-water, Chemical, R/O pre-filter

Descriptions


- CSM jumbo depth filter cartridge is constructed of polypropylene filter media.
- Thermal bonded micro-fiber construction offers no fiber release and consistent flow rates as well as superior filtration performance.
- High dirt holding capacity and excellent flow rates.
- Materials FDA listed as acceptable for potable and edible.
- Available in a wide selection of micron ratings from $0.5\mu\text{m} \sim 100\mu\text{m}$.

Materials

Products	DJ
Media	Polypropylene
Core	Polypropylene

Specifications & Pressure Drop vs Flow Rate

Products		DJ
Length [mm]		750, 1000
Diameter	ID	113mm
	OD	150mm
Max. Temperature		80°C
Max. Differential Pressure		70psi(480kPa) @ 25°C



Ordering Information

Micron Rating

 $1.0 \mu \text{m}$

 $5.0 \mu \text{m}$

 $10.0 \mu \text{m}$ $25.0 \mu \text{m}$

 $50.0 \mu\text{m}$

 $75.0 \mu\text{m}$

 $100.0 \mu \text{m}$

Depth-DJ Cartridge Filter

DJ* 1 2 3

* DJ: D(Depth), J(Jumbo)

No. 3

No. 1

Code 01

05

10

25 50

75

11

No. 2

Code	End Cap
Α	250mm DOE
В	254mm DOE

Code	Length
3	30"
4	40"